

Product	None transfer tamper evident material
Liner	Glassine paper white
Backing	Matt polyester film 0.04mm
Adhesive	Acrylic resin, pressure sensitive
Description	This material will leave a message in the film but not on the surface when attempted to be removed, thus providing unmistakable evidence of tampering. A variety of colours and custom design void messages are available on request. Surface of the material is suitable for various printing methods.
Typical applications	Suitable for HSE surfaces which are to be kept clean of residue
Application temperature	18°C – 25°C (R.H.55% ±5%)

Total Thickness	0.11mm		
Coating Thickness	N.A.		
Temperature resistance	0°C - 80°C		
Initial Tack (PSTC-6 #14 ball)	< 10 cm		
Holding Power (PSTC-7)	> 72 hrs 1 kg/2.5cmx2.5cm		
Peel adhesion to steel (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm
	>1000	>35.2	>9.8

For best result apply with pressure at room temperature on a clean surface and allow some time for reaching optimal bond strength.

The 'x' in the code represents the colour. Standard colours are:

0=Black, 1=Light Blue, 2=Red, 3=Green, 4=Yellow, 5=Silver, 6=Purple, 8=White, 9=Dark red, 10=Orange