



Product Specification

Last updated Jul-10

Page 1 of 1

TM318

Product	Double-Coated PE Foam Tape
Liner	Green PE release film 80μ
Carrier	Closed cell PE Foam, Density 96kg/m ³
Adhesive	Cross-linked solvent acrylic, pressure sensitive
Description	This pressure sensitive mounting tape with solvent acrylic adhesive is suitable for interior as well as exterior applications with high shear performance, holding power and stability. Suitable for use on moderately uneven surfaces.
Range of application	Automotive accessory mounting, interior / exterior trims, towel hooks, exterior display mounting, sign assembly, electronic printing boards
Application temperature	18°C - 25°C

Total Thickness	0.8mm – 0.85mm		
Coating Thickness (Side A/B)	50μ		
Temperature resistance	-20°C - 80°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 6 cm		
Holding Power (Side A/B) (PSTC-7)	> 24 hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 60°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Adhesion (Side A/B) (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm
	>2000	>70.50	>19.5
Solvent resistance	Good		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure max. adhesive contact.

Copyright © 2010 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.