



Product Specification

Last updated Apr-11
Page 1 of 1

DT191

Product	Double coated tissue tape
Liner	White PE paper 110gsm
Carrier	White tissue with a thickness of 0.030mm
Adhesive	High performance solvent acrylic, pressure sensitive
Description	The solvent acrylic adhesive combines high initial tack with good adhesion and cohesive strength. Excellent plasticizer, UV, and chemical resistance. Ones applied moisture resistant.
Typical applications	Laminating to foam and rubber for automotive industry, bonding flexible PVC and vinyl, rough fabrics, mounting badges and nameplates
Application temperature	18°C - 25°C

Total Thickness	0.145mm - 0.155mm		
Coating Thickness (Side A/B)	0.055mm - 0.065mm		
Temperature resistance	-20°C - 200°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	< 5 cm		
Holding Power (Side A/B) (PSTC-7)	> 72 hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 80°C (PSTC-7)	> 24 hrs 0.5kg/2.5cmx2.5cm		
Adhesion (Side A/B) (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm
	>2000	>70.55	>19.50
Solvent resistance	Excellent		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure maximum adhesive contact.

Copyright © 2011 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warrantees, expressed or implied, including the implied warrantees of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.