



Product Specification

Last updated Oct-11
Page 1 of 1

TT6135

Product	Transfer Tape
Liner	Brown Kraft paper liner 130gsm, printed
Carrier	None
Adhesive	Synthetic acrylic resin
Description	Strong cross linked solvent acrylic adhesive offering permanent bonding with good temperature resistance, supported by a strong Kraft paper liner. UL approved.
Typical applications	Circuit boards, mounting of electronic components, membrane switches, nameplates & badges, mounting of automotive accessories.
Application temperature	18°C - 25°C

Coating Thickness	0.130mm - 0.135mm		
Total thickness	0.285mm - 0.290mm		
Temperature resistance	-10°C - 160°C		
Initial Tack (Side A/B) (PSTC-6 #14 ball)	12 - 20 cm		
Holding Power (Side A/B) (PSTC-7)	> 48 Hrs 1 kg/2.5cmx2.5cm		
Holding Power for temperature resistance 195°C (PSTC-7)	> 24 Hrs 1kg/2.5cmx2.5cm		
Adhesion (Side A/B) (PSTC-1)	g/2.5cm	OZ/in	N/2.5cm
	>1500	52.91	>14.60
Shear strength	≥0.25kg/cm ²		

Prior to application the surface should be made dry and free of any dirt, dust and grease. Apply sufficient pressure over the whole surface at room temperature to ensure optimum adhesive contact.

Copyright © 2011 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.