



Product Specification

Last updated February 08

Page 1 of 1

BR15640

Product	Anti-static re-sealable bag sealing tape with PE liner
Liner	HDPE Film, thickness 0.028mm – 0.030mm, printed 'anti-static'
Carrier	Mylar, thickness 0.009mm
Adhesive	Side A: Solvent acrylic / Side B: Water-based Acrylic
Finger-lift	Left hand (L), Centre track (M) or Right hand (R)
Description	Excellent performance perm-peel tape for an easy-to-use re-sealable closure on PE film bags. Suitable for garments as well as food packaging (no chemical reaction / discoloration). This product is available in 1000m, 8000m and 10.000m rolls. Patented anti-static design.
Typical applications	Suitable for sealing OPP bags with or without treatment
Application temperature	18°C - 25°C

Tape thickness	0.055mm		
Temperature resistance	-10°C - 60°C		
Liner width	15mm		
Carrier width	0.625mm		
Adhesive width	Side A: 0.625mm / Side B: 3.5mm		
Holding Power (PSTC-7)	Side A: > 10 Min / Side B: > 3 Min 0.5kg/adhesive widthx2.5cm		
Adhesion to OPP Film side A (PSTC-1)	g/0.625cm	OZ/0.25in	N/0.625cm
	90~120	3.17~4.23	0.88~1.17
Adhesion to OPP Film side B (PSTC-1)	g/0.35cm	OZ/0.14in	N/0.35cm
	65~90	2.29~3.17	0.63~0.88

Prior to application the surface should be made dry and free of any dirt, dust and grease. Use sufficient pressure over the whole surface at room temperature to ensure optimum adhesive contact.

Copyright © 2008 SK Direct (UK) Ltd

All statements, technical information and recommendations are based on tests we believe to be reliable, but the accuracy and completeness thereof is not guaranteed and the following is made in lieu off all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and Manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, User shall determine the suitability of the product for its intended use, and User assumes all risk and liability whatsoever in connection therewith. Seller reserves the right to improve the product and accordingly change the specification without notice. Neither Seller nor Manufacturer shall be liable either in tort or in contract for any loss or damage, direct, incidental or consequential, arising out of the use of or the inability to use the product. No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of or Seller and Manufacturer.